

S-4605

SDI to Optical Converter

SWIT

Introduction:



Specifications:

Input/Output		
Input	BNC × 1	3G/HD/SD-SDI input
Output	BNC × 1	3G/HD/SD-SDI loop output
	LC × 1	Converted Optical fiber output
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080p (30 / 29.97 / 25 / 24 / 23.98)
		1080i (60 / 59.94 / 50)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	ITU-R BT.656	576i (50)
Optical Fiber	SMPTE-125M	480i (59.94)
	SMPTE 297-2006	1310nm wavelength
General		
Power	≤3W	
Working Voltage	DC 6-18V	
Working Environment	Temperature: 0°C-+70°C, Humidity:10%-90%	
Dimensions	98 × 84 × 29 mm	
Net weight	220g	

Features:

- ◆ Portable 3G/HD/SD-SDI to Optical Fiber Converter
- ◆ 1 SDI input, 1 Fiber output, and 1 SDI loop output
- ◆ Single mode Optical Fiber, LC connector
- ◆ Max 20km reliable transmission
- ◆ Support hot swap of the optical module
- ◆ Power / SDI input status indicator
- ◆ Pole-tap 6-18V DC power input
- ◆ Heavy duty aluminium housing
- ◆ Bottom screw threads for installing

SWIT Electronics Co., Ltd.

Website: www.swit.cc
 Email: contact@swit.cc
 Tel: +86 2585805753
 Fax: +86 2585805296

Distributed by: