

LED panel light

SWIT LED panel lights are composed of ultra bright and low power consumption LEDs, featuring high CRI and stable color temperature. With the high intensity technische thermoplaste shell, the lights are ultra lightweight and portable, which makes it perfect for studio lighting.



576 LEDs



**S-2110C Bi-color
S-2110D Daylight**

Features:

- ◆ Small-sized, light-weighted, easy to carry;
- ◆ Dimmable 10%-100%, flicker-free;
- ◆ 50,000 hrs long life ultra bright LEDs
- ◆ Touch-screen LCD controller and rotary knobs for dimming and/or color temperature adjustment;
- ◆ 60° wide beam angle;
- ◆ Power by V-lock/gold mount batteries or supplied AC adapter

S-2110C/S-2120C:

3200K-5600K continuously adjustable

S-2110D/S-2120D:

**5600K daylight output,
3200K with color filter**



1024 LEDs



**S-2120C Bi-color
S-2120D Daylight**

Model	S-2110C	S-2110D	S-2120C	S-2120D
LED	576 LEDs	576 LEDs	1024 LEDs	1024 LEDs
Luminance	3200K : 1500Lux @ 1m 5600K : 1600Lux @ 1m	3200Lux @ 1m	3200K : 2500Lux @ 1m 5600K : 2600Lux @ 1m	5100Lux @ 1m
Beam angle	60°	60°	60°	60°
Color temp	3200K-5600K continuously adjustable	5600K daylight output, 3200K with color filter	3200K-5600K continuously adjustable	5600K daylight output, 3200K with color filter
Output power	≤40W		≤70W	
Work voltage	DC 11-17V, 4pin XLR socket		DC 11-17V, 4pin XLR socket	
Battery mount	V-lock/ gold mount optional		V-lock/ gold mount optional	
Size	403(W)×300(H)×95(D)mm		403(W)×450(H)×95(D)mm	
Weight	1.9kg		2.7kg	
Package	4-leaf barn door, diffuser, AC adaptor, U bracket	4-leaf barn door, diffuser, 3200K filter, AC adaptor, U bracket	4-leaf barn door, diffuser, AC adaptor, U bracket	4-leaf barn door, diffuser, 3200K filter, AC adaptor, U bracket