

Multi-sockets Square Li-ion Battery

PB-S series camera batteries are compact designed, shorter than normal V/Gold mount batteries, and match perfectly with most of the Cine-cameras.

The build-in OLED can display accurate power info during charging and discharging, and support viewfinder info display on both SONY and RED cameras.

To make convenient connections, the PB-S batteries provide USB output socket and up to 4 D-tap sockets for camera-top devices.



PB-S98A/S 98Wh

- ◆ Square shape design for Cine-cameras
- ◆ Max 150W, 12A high load
- ◆ 2× D-tap output sockets
- ◆ 1× USB 5V/2A power output sockets
- ◆ OLED display accurate remaining run time
- ◆ Display power info in both SONY & RED
- ◆ Multiple circuit protections

PB-S98A: Gold mount

PB-S98S: V-mount

Model	PB-S98S	PB-S98A
Battery plate	V-mount	Gold-mount
Nominal voltage	14.4V	14.4V
Capacity	98Wh,6.8Ah	98Wh,6.8Ah
Max output	Electrodes	150W,12A
	D-TAP	120W,10A
	USB	10W,5V/2A
	In total	150W
Dimension	121×95×59mm	121×95×62mm
Net weight	0.809kg	0.800kg
Max charging current	3A	3A
D-TAP socket number	2	2
USB socket number	1	1



Power info display – The OLED displays remaining power percentage, remaining working time, low power warning, and battery cycle times.



Display power percentage when the battery is free or during charging. Lightning icon is displayed during charging.



Display remaining running time when the battery is powering on camera or any devices. Press power check button can switch to power percentage display.



If the working time is less than ten hours, it will display 0~9:59; If the working time is more than 10 hours, it will display remaining working hours.



Long press power check button for 5 seconds, it will display battery cycle times.